

Westinghouse



AD 675771

WORLD-WIDE
VLF EFFECTIVE-CONDUCTIVITY
MAP

80133F-1

AD 675771

Reproduction in whole or in part is permitted for
any purpose of the United States Government.

Submitted to: Office of Naval Research
Department of the Navy
Washington, D. C. 20360
Under contract N00014-67-C-0274

15 January 1968

Robert R. Morgan

WORLD-WIDE
VLF EFFECTIVE-CONDUCTIVITY
MAP

Westinghouse Electric Corporation
Environmental Science and Technology Department

ABSTRACT

A map showing effective electrical earth conductivity values for a propagating wave at VLF (10 kHz to 30 kHz) has been prepared for the major land areas of the world. Land area conductivity determinations were in most cases based upon known geological and climatological information. Actual conductivity data was collected where possible to aid in determining regional effective conductivity values, but the correlation between geology (and other known factors), and conductivity was used in estimating conductivity for the majority of the land areas.

The conductivity data are overprinted on seven 17 × 22 inch base maps. Effective conductivity values are designated by numbers from 1 to 10 referenced to a legend on each sheet. Separate page-size maps showing a confidence factor and a variability factor are included in the accompanying report.

TABLE OF CONTENTS

Section	Page
1.0 INTRODUCTION	1
2.0 DESCRIPTION AND USE OF MAP	3
3.0 EFFECTIVE CONDUCTIVITY	19
4.0 ACCURACY OF MAP	21
REFERENCES	24

LIST OF ILLUSTRATIONS

	Page
Figure 1	Confidence and Variability Factors for North America 4- 5
Figure 2	Confidence and Variability Factors for South America 6- 7
Figure 3	Confidence and Variability Factors for Europe 8- 9
Figure 4	Confidence and Variability Factors for Africa 10 11
Figure 5	Confidence and Variability Factors for Asia 12-13
Figure 6	Confidence and Variability Factors for Australia 14-15
Figure 7	Confidence and Variability Factors for Antarctica 16-17
Figure 8	Conductivity Map of Canada 22
Figure 9	Revised Conductivity Map of Canada (Revision by NRL is on the basis of propagation measurements) 23

WORLD-WIDE VLF EFFECTIVE-CONDUCTIVITY MAP

1.0 INTRODUCTION

A map showing effective electrical conductivity of the earth at very low frequencies (10 kHz to 30 kHz) has been prepared to aid in radio propagation and navigational studies. Values of conductivity were determined for land areas whose boundaries are in most cases based upon climatological, pedological, physiographical, and geological information. Data was collected to aid in establishing regional effective-conductivity values. It was necessary, however, to rely on the correlation between geology and other known environmental factors and conductivity for the majority of the land areas [1].

It is noteworthy that there is considerable difference between effective-conductivity maps for use at broadcast frequencies (1 MHz) and the VLF map: these differences are due primarily to the greater depth of penetration of the VLF energy. Earth materials to depths of over 50 meters must be considered for conductivities on the order of 10^{-2} mho/meter, and greater depths of penetration are involved for lower conductivities.

Because of the relationships between conductivity and phase velocity, and between conductivity and attenuation rate, it is much more important to accurately determine conductivities which are below 10^{-3} mho/meter than to accurately determine conductivities which are 10^{-2} mho/meter and greater, hence, the lack of detail on the maps for this latter conductivity range. Materials which fall into the lower, more

important range include geologically old, crystalline rocks. Areas where permafrost occurs, and areas with ice caps (Greenland and the Antarctic) are similarly important. Measurements were made in permafrost areas of the Canadian Shield during an earlier program which produced the conductivity map of North America to help define the effect of freezing on the in situ electrical properties of the rocks [2].

The author would like to acknowledge the assistance of Mr. Gary Aho, during the summer of 1967, who shared a large part of the responsibility for the project during that time. The author is indebted to the many scientists and research organizations who sent hundreds of replies to requests for electrical conductivity data. Of particular help in this data collection effort were the United States Embassies throughout the world. Plans are to publish additional material which can include a list of contributors. It is hoped that contributors will continue to send data as it becomes available, and that future editions of the map will therefore be of increased usefulness to the scientific community throughout the world.

2.0 DESCRIPTION AND USE OF MAP

The conductivity map is overprinted on seven 17 X 22 inch base maps supplied by Bonn Cartographic Corporation of Salt Lake City, Utah. The effective-conductivity values are designated by numbers 1 to 10, referenced to a legend on each sheet.

Since little appropriate VLF data exists on a world-wide basis, it is not possible to evaluate directly the accuracy of the entire map. As an alternative, two factors directly related to the reported values are presented. The Confidence Factor refers to the quality, quantity and type of information which determined the regional conductivity values. The Variability Factor indicates the amount by which local values of conductivity can be expected to vary from the regional average.

The above two factors are seen to be independent, and are presented separately for each sheet of the map in Figures 1 through 7. These factors are distinguished as follows:

Confidence Factor

Highest Confidence: Correlation based on sound geologic and conductivity data. These values are not expected to change appreciably from the reported values.

Moderate Confidence: Some data available. Geology-conductivity correlation believed to be reliable. These values will probably not need to be revised by more than one level (one half decade).

Limited Confidence: Geology-conductivity correlation not well known. Some data may be available, but it is limited in quantity or quality. These values may change as data becomes available.




Figure 1A Confidence Factor for North America




Figure 1B Variability Factor for North America




Figure 2A Confidence Factor for South America




Figure 2B Variability Factor for South America




Figure 3A Confidence Factor for Europe




Figure 38 Variability Factor for Europe




Figure 4A Confidence Factor for Africa




Figure 4B Variability Factor for Africa




Figure 5A Confidence Factor for Asia




Figure 5B Variability Factor for Asia




Figure 6A Confidence Factor for Australia




Figure 68 Variability Factor for Australia




Figure 7A Confidence Factor for Antarctica




Figure 78 Variability Factor for Antarctica

Estimates Only: Estimates based on extrapolations of known correlations, or on knowledge of conduction mechanisms. These are areas where data is most needed.

Variability Factor

Highly Variable: Variations in local conductivity may be \pm one decade or more from the average regional value.

Moderately Variable: less than \pm one decade.

Slightly Variable: less than \pm half decade.

Important factors relating to the use of the map include effects of "closed lines" where it is evident that energy spreading and defraction can result in less attenuation than would be obtained for a "straight" path between receiver and transmitter. Similarly, transmission across a narrow conductivity contrast which the energy may not circumvent may result in more attenuation than predicted because of energy conversion, reflection, and scattering. Similar effects may be experienced over high rugged mountains, and effects equivalent to one order of magnitude (smaller conductivity) than that attributed to the electrical properties of the materials have been observed for paths across the length of mountain chains. Users should consider the above items in light of the Fresnel spreading of the propagating energy, and the conductivity profile for a propagation path should be determined consistent with this concept, i.e., it is suggested that users consider values of earth conductivity over an area representing the width of the path rather than along a very narrow "line" (great circle) [3].

3.0 EFFECTIVE CONDUCTIVITY

Effective conductivity of a region is defined as the conductivity of a plane, uniform, homogeneous earth which would have the same effect on a propagating electromagnetic field as that of the region. Complications arise for instances where displacement currents in the earth become comparable in magnitude to conduction currents [4] and also for cases where lateral changes result in an anisotropic conductivity in the plane of the surface. These effects were not accounted for in this present work:

1. In most of the land areas of the world, the earth approximates a conductor. Limited data indicate that even for the Greenland Ice Cap, the conduction currents are probably dominant over displacement currents at 10 kHz [5].
2. Only in a few areas was there sufficient data to indicate a difference in conductivity with compass direction. The additional complication of the maps does not justify including this.

Where there was enough information, the magnitude of effective (complex) conductivity was computed for a horizontal layered case [2, Appendix A, also see reference 6].

4.0 ACCURACY OF MAP

Some estimation of the accuracy of the maps for VLF propagation studies may be gained from a comparison of Figures 8 and 9. Figure 8 is a portion of the map of North America, which was produced in 1965 [2]. This map is essentially identical to the northern portion of Sheet 1. Figure 9 shows a revised map based on VLF propagation measurements made in September 1959 and August 1961 (these maps were provided by the U.S. Naval Research Laboratory). Note two significant changes suggested by the NRL Map:

1. The boundary of the "3" region northwest of Hudson Bay should extend further north. This may indicate that the extent of continuous permafrost is further north than previously estimated, or that a thicker deposit of conducting overburden exists in this area.
2. There is an area of "2" conductivity, 3×10^{-5} mho/m, between Labrador and Hudson Bay. This is most likely due to a previously unrecognized occurrence of continuous permafrost. If this area had been so designated, it is noted that the conductivity would have been estimated as 1×10^{-4} mho/m rather than the 3×10^{-5} mho/m as indicated by the NRL Map. Measurements of earth conductivity in this area are therefore suggested.

Other areas can be expected to undergo similar revisions when more data is obtained. These revisions are not expected to be of significance for regions indicated as "highest confidence." Areas similar to the Canadian Shield region which are not well known geologically, and where there is only limited information on permafrost extent and thickness, can be expected to undergo the most extensive revisions.

Further discussion, a list of contributors, etc., may be found in the Appendices which accompany the larger report.




Figure 8 Conductivity Map of Canada.




Figure 9 Revised Conductivity Map of Canada. Revision by NRL
is Based on Documentation Measurements

REFERENCES

- [1] Card, R. H., Correlation of Earth Resistivity with Geologic Structure, Trans. AIME, V 138, pp 380-398, 1940.
- [2] Morgan, R. R. and E. L. Maxwell, Omega Navigational System Conductivity Map, DECO Report 54-F-1, December 1965, under contract NONr 4107(00).
- [3] Watt, A. D., VLF Radio Engineering, Pergamon Press, New York 1967.
- [4] Wait, J. R., The Propagation of Electromagnetic Waves Along the Earth's Surface, appearing in Electromagnetic Waves, R.E. Langer, editor, University of Wisconsin Press, 1962.
- [5] Watt, A. D. and E. L. Maxwell, Measured Electrical Properties of Snow and Glacial Ice, NBS Journal of Research, 64D, July-August 1960.
- [6] Wait, J. R., Electromagnetic Waves in Stratified Media, Pergamon Press, London, 1962.

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
Westinghouse Electric Corporation		Unclassified	
		2b. GROUP	
3. REPORT TITLE			
World-wide VLF Effective-Conductivity Map			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
Technical Report			
5. AUTHOR(S) (Last name, first name, initial)			
Morgan, Robert R.			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
15 January 1968		24	6
8a. CONTRACT OR GRANT NO.		8b. ORIGINATOR'S REPORT NUMBER(S)	
N0014-67-C-0274		80133F-1	
a. PROJECT NO.			
c.		9a. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		None	
10. AVAILABILITY/LIMITATION NOTICES			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		Office of Naval Research Department of the Navy	
13. ABSTRACT			
<p>✓ A map showing effective electrical earth conductivity values for a propagating wave at VLF (10 kHz to 30 kHz) has been prepared for the major land areas of the world. Land area conductivity determinations were in most cases based upon known geological and climatological information. Actual conductivity data was collected where possible to aid in determining regional effective conductivity values, but the correlation between geology (and other known factors), and conductivity was used in estimating conductivity for the majority of the land areas.</p> <p>The conductivity data are overprinted on seven 17 X 22 inch base maps. Effective conductivity values are designated by numbers from 1 to 10 referenced to a legend on each sheet. Separate page-size maps showing a confidence factor and a variability factor are included in the accompanying report.</p>			

DD FORM 1473
1 JAN 64

Security Classification

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Effective Electrical Earth Conductivity Correlation Between Geology and Conductivity VLF Effective Conductivity Maps						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.


13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).


There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.


14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, rules, and weights is optional.

Security Classification



ANTARCTICA






Symbol	Effective VLF Conductivity σ_{\bullet} (mho/m)
①	1×10^{-5}
②	3×10^{-5}
③	1×10^{-4}
④	3×10^{-4}
⑤	1×10^{-3}
⑥	3×10^{-3}
⑦	1×10^{-2}
⑧	3×10^{-2}
⑨	1×10^{-1}
⑩	4

LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

SCALE 1:12.5

0 100 200

0 100 200 500




Note: The Conductivity Boundary Between Sea Water and Shelf Ice may be Gradational, and is not Accurately Known. The Magnitude of the (Complex) Conductivity of the Ice Sheet is Estimated to be 1×10^{-5} mho/m. Neglecting Possible Increase in ϵ with Pressure, Displacement Currents are Expected to be Negligible Compared to Conduction Currents at VLF. See Note on Sheet 1

SCALE 1:12,500,000


Base Map COPYRIGHT BY BONN CARTOGRAPHIC CORPORATION
SALT LAKE CITY

100 200 300 400 500 MILES
500 1000 KILOMETERS

A





B



C

AUSTRALIA





Symbol	Effective VLF Conductivity σ_e , (mho/m)
①	1×10^{-5}
②	3×10^{-5}
③	1×10^{-4}
④	3×10^{-4}
⑤	1×10^{-3}
⑥	3×10^{-3}
⑦	1×10^{-2}
⑧	3×10^{-2}
⑨	1×10^{-1}
⑩	4


World-Wide Very-Low-Frequency
 Effective-Conductivity Map

January, 1968 R.R. Morgan
 Sheet 6 of 7

Refer to Westinghouse Report 80133 F-1
 for information relating to the use of this Map.

LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

D



Frequency Map


R. Morgan

F 7


80133 F-1

The use of this Map.

SCALE 1:12,000,000




E





Base Map by BONN CARTOGRAPHIC CORPORATION

KILOMETERS

F









LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

SCALE 1:1






Scale 1:22,000,000

Base Map by BONN CARTOGRAPHIC CORPORATION

500 1000 MILES

1000 1500 2000 KILOMETERS



AFRICA

20° East Longitude


30°


40°

50°

60°


Note: Refer to Sheet 3 for Conductivity Values of Europe






LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

SCALE 1:21,000,000






SCALE 1:21,000,000


500 1000 MILES
1000 2000 KILOMETERS

Base Map COPYRIGHT BY BONN CARTOGRAPHIC CORPORATION
SALT LAKE CITY


A




B




EUROPE





LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

D




SCALE 1:12,500,000

0 100 200 300 400 500 MILES


0 500 1000 KILOMETERS

E





Base Map COPYRIGHT BY BONN CARTOGRAPHIC
SALT LAKE CITY

F



SOUTH AMERICA





Symbol	Effective VLF Conductivity σ_e , (mho/m)
①	1×10^{-5}
②	3×10^{-5}
③	1×10^{-4}
④	3×10^{-4}
⑤	1×10^{-3}
⑥	3×10^{-3}
⑦	1×10^{-2}
⑧	3×10^{-2}
⑨	1×10^{-1}
⑩	4

World-Wide Very-Low-Frequency
 Effective-Conductivity Map


January, 1968 R.R. Morgan
 Sheet 2 of 7

Refer to Westinghouse Report 80133 F-1
 for Information Relating to the use of this Map.




SINUSOIDAL PROJECTION

SCALE 1:20,000,000



C



SCALE 1:20,000,000

Base Map COPYRIGHT BY BONN CARTOGRAPHIC CORPORATION
SALT LAKE CITY


500

1000 MILES


1000

2000 KILOMETERS


D



NORTH AMERICA



Symbol	Effective VLF Conductivity σ_e , (mho/m)
①	1×10^{-5}
②	3×10^{-5}
③	1×10^{-4}
④	3×10^{-4}
⑤	1×10^{-3}
⑥	3×10^{-3}
⑦	1×10^{-2}
⑧	3×10^{-2}
⑨	1×10^{-1}
⑩	4



**World-Wide Very-Low-Frequency
Effective-Conductivity Map**



January, 1968 R.R. Morgan
Sheet 1 of 7


Refer to Westinghouse Report 80133 F-1
for Information Relating to the use of this Map.

Note: A Value of 10 was Obtained for the Relative Dielectric Constant at the Surface of the Greenland Ice Cap at VLF. Neglecting Possible Increase in ϵ with Pressure, the Displacement Currents are Expected to be Negligible Compared to the Conduction Currents at These Frequencies.


(See Memorandum NBS PM-85-30, 1959 Measured Electrical Properties of Snow and Glacial ice (Addendum) by A.D. Watt and E.L. Maxwell.)

LAMBERT AZIMUTHAL EQUAL AREA PROJECTION

SCALE 1:20,000,000




C



104-2

SCALE 1:20,000,000

Base Map COPYRIGHT BY BONN CARTOGRAPHIC CORPORATION
SALT LAKE CITY



D